

What is claimed is:

1. An image processing apparatus having an image
reading unit for reading an image per line from a sheet-like
recording medium by applying a laser beam to the sheet-like
recording medium and scanning the sheet-like recording
medium with the laser beam in a main scanning direction,
comprising:

a controller dedicated for controlling reading of the
image from the sheet-like recording medium, said controller
being operable in synchronism with a main scanning
synchronizing signal supplied thereto.

2. An image processing apparatus according to claim 1,
wherein said controller comprises means for performing
shading correction on the image to be read in at least an
effective reading period in a period of reading one line of
image.

3. An image processing apparatus according to claim 1,
wherein said controller comprises means for detecting at
least an error in an ineffective reading period in a period
of reading one line of image.

4. An image processing apparatus according to claim 3,
wherein said error-detecting means includes means for
measuring the period of said main scanning synchronizing

signal.

5. An image processing apparatus according to claim 1,
further comprising:

5 an erasing unit for erasing image information carried
on said sheet-like recording medium after said image is read
therefrom;

10 said controller comprising means for detecting an
erasing level for said erasing unit in an ineffective
reading period in a period of reading one line of image.

15 6. An image processing apparatus according to claim 5,
wherein said erasing-level detecting means includes means
for holding a maximum value of the level of an image signal
from the line to be read.

20 7. An image processing apparatus according to claim 2,
wherein said shading-correction performing means comprises:

 means for outputting shading corrective data in
synchronism with a reference clock signal;

 means for converting the outputted shading corrective
data from digital data into an analog corrective signal; and

 means for adding an image signal representing the read
image and said analog corrective signal to each other.

25 8. An image processing apparatus according to claim 2,
wherein said shading-correction performing means comprises:

means for converting an image signal representing the read image from analog image data into digital image data;

means for reading shading corrective data in synchronism with a reference clock signal;

means for adding said digital image data and said shading corrective data into combined data; and

means for outputting the combined data.

9. An image processing apparatus according to claim 2, further comprising:

a deflector for deflecting the laser beam to scan said sheet-like recording medium in the main scanning direction while the laser beam is being applied to said sheet-like recording medium, said deflector having a plurality of facets,

said shading-correction performing means performing shading correction depending on facet characteristics of each of said facets of the deflector.

10. An image processing apparatus according to claim 1, wherein said controller comprises means for generating a signal to manage displaying of the image in synchronism with said main scanning synchronizing signal.